

# EPSS

European Printer Support Services GmbH

## DTP216-PS

**A4 Thermal Direct PCL & PDF-Document Printer**



- ◆ Autonomous direct PCL & PDF printing – no driver installation
- ◆ Fast A4 thermal direct printer
- ◆ Auto paper loading
- ◆ No warm-up, instant print start
- ◆ Very small footprint, 32cm x 19 cm only
- ◆ Long-lasting print head, about 300.000 pages A4 fan fold paper
- ◆ Full metal cabinet
- ◆ Cost-saving spare head
- ◆ Ethernet IF

## Technical Data DTP216-PS

<b>Print mode</b>	Thermal direct
<b>Print head</b>	Max. 100 km mileage
<b>Resolution</b>	8 dots/mm (200 dpi)
<b>CPU</b>	32 Bit
<b>Linux based print server</b>	Administration via network
<b>Print speed</b>	100 mm/s (4 IPS)
<b>Print length</b>	Min. 80 mm - max. 297 mm
<b>Print width</b>	Max. 216 mm (8.5 ")
<b>Sensor</b>	Sensor for black mark and paper out detection
<b>Paper processing</b>	Black mark and continuous feed (Sensor standard position is left, centre or right as factory option)
<b>Paper properties</b>	Width: 210 mm ~ 216 mm Thickness: 0.06 mm ~ 0.1 mm
<b>Printer language</b>	PDF & (HP PCL5 as option)
<b>Interface</b>	Ethernet 2.0
<b>Ethernet protocol</b>	DHCP, TCP/IP
<b>Control Panel</b>	Status LEDs for POWER-ON, ERROR and PAPER-OUT Control keys for RESET and FEED
<b>Power</b>	100V ~ 240V, 50 ~ 60 Hz, max. 70 W
<b>Conformity</b>	CE
<b>Operating environment</b>	5°C ~ 45°C, 20% ~ 90% RH at 40°C
<b>Storage environment</b>	-40°C ~ 60°C, 20% ~ 93% RH at 40°C
<b>Weight</b>	5.5 kg
<b>Dimension</b>	Width : 330 mm Height: 158mm Depth : 140mm, 190 mm with paper feed tray

Technical data is subject to change without notice.

All company and/or product names are trademarks and/or registered trademarks of their respective owners.

© 01.2014 EPSS